

TRAMFLOC, INC.

6046 FM 2920 Road #615, Spring, TX 77379-25420 Voice: 888-929-8973 Fax: 480-383-6895

Technical Information Bulletin

TRAMFLOC® 860A COAGULANT & DEMULSIFIER

Product Description

Tramfloc® 860A is a low molecular weight and low viscosity, 50% active polyamine product with NSF® standard 60 approval. Tramfloc® 860A has proven efficacy in resolving oil in water and inverse emulsions. This formulation is also useful in separating fines in potable water, lime softening, dye and ink production, food processing, drilling fluids' resolution and bio-pharma streams.

Uses

Tramfloc® 860A is highly effective in a variety of oil/water/solids separation processes in industrial, refining, chemical, mining, paper making, and utility applications. Tramfloc® 860A helps produce high clarity water, a dense rag layer and a clean, high quality oil phase in demulsification applications in oil recycling and recovery operations. For optimum results, the coagulated material may require flocculation by another Tramfloc® formulation. Tramfloc® 860A is also used to reduce the application of inorganic coagulants such as iron and aluminum salts, lime and clays.

Feeding

Tramfloc® 860A is usually metered to a point of good mixing in the application either neat or diluted.

Packaging

Tramfloc® 860A is available in 232 kgs drums, IBC's and in bulk.

Safety and Health

Spills of coagulants are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Tramfloc® Cleaner 348 can be used to remove residue from equipment and floors. Coagulants can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Precaution should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.